



## INSTALLATION AND MAINTENANCE Bins

### INSTALLATION

- All bins should be mounted level to the ground. Packing may be required due to inconsistencies in the footpath.
- 10mm Dyna bolts are used for securing all bins.



### Timber Battens (Aston Bin)

- Regular inspections of the timber should be carried out every 3 – 6 months to check for any damage or wear and tear to the finished surface.
- We recommend washing the timber down with water and detergent. Any damage to the timber or break in the protective clear coat will need to be repaired.
- The timber should be gently sanded back and a new clear coat applied. If necessary, the area may need freshening up with a coat of natural stain prior to clear coating.
- This method can be used to repair just a small area or to repair the entire length of the batten if necessary.
- We recommend light sanding and re staining should occur annually to maintain the look of your bin.
- We use Intergrain Natural Stain New Merbau Kwila and Feast and Watsons Marine Grade all weather proof clear coat.



### Powder Coat Care

- Powder coated bin components that become dull due to prolonged exposure to direct sunlight can be restored with an appropriate surface polish.
- Regular washing down of the powder coated surface will help prolong the lustre of the powder coated finish.
- Do not use any solvents on the surface as this will adversely affect the longevity of the powder coated finish.
- Surface scratches and inconsistencies can be touched up using Dulux touch up paint. Most colours can be matched.



### Bolts

- Mounting bolts should be checked monthly to ensure they are secure.
- We recommend using loctite to help secure the nuts in place.

### Bin Locks/Pivot Points

- We recommend using WD40 spray can to lubricate pivot points and locking mechanisms every 6 months.

### Spare Parts

- All bin components are available individually from our service department.
- We offer a full parts and technical back up service of all our products.

