



INSTALLATION AND MAINTENANCE PB150



- Flushing of inlet water pipe is essential before connecting to the fountain to help prevent blockage caused by debris.
- When installing all local and state plumbing codes should be adhered to.
- Installer must provide trap for proper installation.
- Must be installed by a qualified plumber.
- Incorrect installation will affect fountain performance.
- Urban Fountains and Furniture will not be responsible for defects that arise from incorrect installation.
- All fountains are water tested prior to leaving the factory.
- Locktighting of foundation cage bolts is recommended.
- Regular polishing with a non-abrasive polish will help maintain the exterior of the fountain.
- To maintain easy access over long periods of time, we recommend the use of anti-seize paste on all external bolt threads.
- Always ensure the correct security screwdriver is used when undoing external bolts.
- Each fountain is fitted with a water pressure regulator and the manufacturer's information brochure is supplied with each fountain for referral.
- All maintenance tools and replacement parts can be purchased individually from the manufacturer.
- Regular checking of the basin and nozzle for debris and prompt removal of such debris will prolong the working life of the fountain.

Exterior care

- Painted fountains that become dull due to prolonged exposure to direct sunlight can be restored with an appropriate surface polish.
- Regular washing down of the exterior surface will help prolong the lustre of the painted finish.
- Do not use any solvents on the surface as this will adversely affect the longevity of the painted finish.
- Surface scratches and inconsistencies can be touched up using Dulux touch up paint. Most colours can be matched.

For any advice or concerns please contact Urban Fountains and Furniture.

