



INSTALLATION AND MAINTENANCE Tree Grates

INSTALLATION

- Ensure that the frame is installed level with the existing footpath.
- Frame should be installed flat (as supplied), free from any twists. If the frame is installed incorrectly the tree grate will not sit correctly in the frame.
- When concreting frame in place, ensure there is enough clearance under corner bar supports for cam lock to slide in to.
- Ensure that the surface that the grate is to sit on remains free of debris before installing grate.
- We recommend 5mm pea gravel to be placed under the grate for added support and weed control.
- Ensure cam locks and bolts are securely tightened. A 10mm socket is all that is required to secure cam locks.

MAINTENANCE

- Regular checking of tree grates for damage and ensuring all bolts are securely tightened should be carried out every 3 – 6 months.
- We recommend removing grates and clearing leaves and rubbish that has collected every 3 – 6 months. This is made easy by our quick release cam lock system.
- Grates that become damaged due to vehicle impact should be repaired or replaced as they may become a trip hazard to pedestrians.

Powder Coat Care

- Powder coated grates that become dull due to prolonged exposure to direct sunlight can be restored with an appropriate surface polish.
- Regular washing down of the powder coated surface will help prolong the lustre of the powder coated finish.
- Do not use any solvents on the surface as this will adversely affect the longevity of the powder coated finish.
- Surface scratches and inconsistencies can be touched up using Dulux touch up paint. Most colours can be matched.

